



HEPOS

The Hellenic RTK-Network

Dr. Michail Gianniu
Head of Geodetic Department
KTIMATOLOGIO S.A. (Hellenic Cadastre)



Overview



- **Realization Framework**
- **Realization Strategy**
- **Timetable**
- **Preparation related issues**
- **Establishment related issues**
- **System Description**
- **Proven Solutions**
- **Geodetic Aspects**
- **Geodynamic Aspects**
- **First Performance Tests**

Chosen Approach

One Tender for delivering a complete system

+

Initial operation of the system by the contractor

=

DBO (Design – Build – Operate) Approach

Advantages of DBO Approach

- Technical Specifications are compact (functionality of the system can be directly requested)
- Risk reduction: only one tender
- The good operation of the system is guaranteed to a high degree
- Tuning of system is easier (only one contractor)
- Easier to supervise the contract
- Have control over the running costs of the system, as they are included in the economical offer

Timetable

Trimble
DIMENSIONS 2007

- **12/2003: Decision made to implement HEPOS**
- **07/2005: Completion of system design & tender documents**
- **08/2005: Start of public consultation**
- **10/2005: Tender announcement**
- **01/2007: Contract awarded to Trimble Europe B.V.**
- **05/2007: Installation of first Reference Station**
- **08/2007: Installation of 98 Reference Stations & Control Center completed**
- **11/2007: End of system setup & workout period**
- **12/2007: Planned to be available to the users**

Preparation related issues

Trimble
DIMENSIONS 2007

Design and register trademark



Register www site name

www.hepos.gr

Preparation related issues

Trimble
DIMENSIONS 2007

Legal Issues

- **Modification of Building Regulations to allow installation of the antennas**
- **Determine the terms of contracts for leasing the buildings of the Reference Stations**

Preparation related issues

Trimble
DIMENSIONS 2007

Selection of Station Sites


- **Rough terrain of Greece implies serious restrictions in the site selection**
- **A GIS Application has been developed for checking the satellite visibility on a desired site**
- **The application allowed the selection of sites in the office**

Preparation related issues


Trimble
DIMENSIONS 2007

Visibility check (Elevation Mask: 5 deg)

Unacceptable site




Acceptable site



Preparation related issues

Trimble
DIMENSIONS 2007



Network design according to the specifications:

- Net 1
- Net 2
- Single Ref. Stations


(Uncovered area in the northern part is deep forest)

Establishment related issues

Trimble
DIMENSIONS 2007

Satellite Visibility

Part of the documentation delivered by the contractor to get approval for installation



Establishment related issues

Trimble
DIMENSIONS 2007

Antenna mounts


Roof-mounted



Wall-mounted



Roof mount: Procedure followed by contractor



ΣΧΗΜΑΤΙΚΗ ΤΟΜΗ ΑΠΟΚΑΤΑΣΤΑΣΗΣ ΜΟΝΩΣΗΣ ΜΕΤΑ ΤΗΝ ΕΓΚΑΤΑΣΤΑΣΗ ΜΑΖΤΟΥ ΚΕΡΑΜΑΖ GPS




Roof mount: Procedure followed by contractor



System description: Network

Trimble
DIMENSIONS 2007



HEPOS Complete Network

Networked RS: 87

Single RS : 11

Total RS : 98

System description: Ref. Stations

Trimble
DIMENSIONS 2007



Buildings:
controlled access

System description: Ref. Stations

Trimble
DIMENSIONS 2007



Buildings:

Alarm devices

Lightning protection

System description: Ref. Stations

Trimble
DIMENSIONS 2007



Mast:

Stainless

Diameter: 10cm

Grounded

Always fixed on concrete

System description: Ref. Stations

Trimble
DIMENSIONS 2007

Antennas: Trimble Zephyr Geodetic with Dome



System description: Ref. Stations

Trimble
DIMENSIONS 2007



Aluminum tribrach:
Designed by the contractor



System description: Ref. Stations

Trimble
DIMENSIONS 2007



Station & contact Info



UPS

System description: Ref. Stations


Trimble
DIMENSIONS 2007

GPS Receiver:
Trimble Net RS

NPS

GSM/GPRS
Modem

Router



Cabin Fans

Fans
Thermostat


Serial Modem

ISDN Modem

System description: Ref. Stations

Trimble
DIMENSIONS 2007

NPS: Network Power Switch



All devices can be powered-up or restarted remotely from the Control Center.

This:

- Saves expenses for visiting RS
- Saves time for visiting RS
- Increases availability of services

System description: Control Center

Trimble
DIMENSIONS 2007

GPS Receiver at CC
Firewall
Router
VPN Concentrator
Access Server
Network switch
Application servers
Backup device
Storage server
UPS
Battery Packs (2/6)



Terminal



System description

Trimble
DIMENSIONS 2007

Telecom Network

- **Main Lines:**
 - MPLS VPN ADSL
 - MPLS VPN ISDN (in few sites without ADSL availability)
- **Back-up lines:**
 - GSM/GPRS
- **GSM users support:**
 - Hardware capable of supporting 480 parallel GSM users
 - Lines for supporting 60 parallel GSM users
- **GPRS users support:**
 - Currently capable of supporting 150 parallel user, as required by the specifications. Expansion capabilities with additional licenses.

System description

Trimble
DIMENSIONS 2007

Offered Services

APPLICATION	SERVICE	DATA FORMAT
Post Processing	RS data	RINEX, CRINEX
	VRS data	RINEX, CRINEX
Real Time	Network RTK: VRS	RTCM 2.3
	Network RTK: FKP	RTCM 3.0
	Network RTK: MAC	RTCM 3.1
	Single Base RTK	CMR+
	Network DGPS	RTCM 2.3
	Single Base DGPS	RTCM 2.3

Strategic Decisions

- **Strategic partner for hosting the reference stations**
reduces delays during installation, facilitates logistics
- **Choosing DBO Approach**
Profit by all DBO advantages mentioned before

Technical & Practical Issues

- **Rack mounted devices in the control center:**
Avoiding “computer pool”
- **NPS at the Reference Stations:**
All devices can be rebooted form Control Center
- **Reference Station at Control Center**
Good reference for data latencies
- **Contact info on the cabin at the reference sites**
Avoid unwanted interventions
- **ADSL/ISDN router**
No need to visit RS when ISDN is replaced by ADSL

Requirements

- **HEPOS should realize the national Coordinate Reference System (GGRS'87: Greek Geodetic Reference System 1987)**
- **HEPOS must be able to realize a new geodetic datum that can replace the existing one in the future**

Steps for fulfilling requirements

- **A nation-wide GPS Campaign has been made for establishing transformation parameters between GGRS87 and the reference frame of HEPOS**
- **Use a realization of ETRS'89 as the reference frame of HEPOS**

GPS Campaign

- 2500 points of the National Trigonometric Network have been measured, i.e 10% of the total number of points
- Points are evenly distributed all over the country

GPS Campaign






**GPS Campaign:
Measured points**

Transformations

- **7 parameter Helmert transformation sets are computed for each map sheet 1:50.000 and 1:100.000 (map sheets chosen due to historical reasons)**
- **Correction grids are computed over a nation-wide transformation set**
- **Evaluation of these models will lead to the final transformation model**

Geodetic Aspects

Trimble
DIMENSIONS 2007



Transformations


Residuals of 7parameter Helmert transformation (North Greece):

Typical behavior of a conventional trigonometric network

Geodynamic Aspects

Trimble
DIMENSIONS 2007

EUREF Permanent Tracking Network



ETRS89:

By definition is fixed to the stable part of the Eurasian Plate

Geodynamic Aspects

Velocities of EPN stations (ETRF2005)


STATION	VX_{EPN} (m/y)	VY_{EPN} (m/y)	VZ_{EPN} (m/y)	$ V _{EPN}$ (m/y)
WTZR	0.0001	0.0003	0.0006	0.0007
GRAZ	-0.0003	0.0007	0.0008	0.0011
KOSG	0.0005	0.0003	0.0011	0.0012
AUT1	0.0049	0.0033	-0.0079	0.0099
NOA1	0.0125	-0.0118	-0.0211	0.0272
TUC2	0.0196	-0.0096	-0.0208	0.0301

Geodynamic Aspects

Remarks

- An initial period of operation of HEPOS is necessary for revealing the rate of change of RS coordinates throughout the country
- The differential rate of change between neighboring stations is of particular importance
- The network should treat the changes in a way that the stability of the planar coordinates is guaranteed

First Performance Tests



Multipath estimation at RS:

The plots prove very low multipath effect

First Performance Tests



Synchronizer (all) Status				
Synchronized output (Time/Stations)				
ID	Station	Received	Delay [s]	Avg Delay [s] (E.P.)
9	009A	7/9/2007 6:33:06 nu	0.484	0.331 (55848)
22	022A	7/9/2007 6:33:06 nu	0.500	0.310 (55848)
80	080A	7/9/2007 6:33:06 nu	0.500	0.290 (55843)
56	056A	7/9/2007 6:33:06 nu	0.500	0.286 (55848)
35	035A	7/9/2007 6:33:06 nu	0.484	0.285 (55848)
21	021A	7/9/2007 6:33:06 nu	0.500	0.279 (55848)
91	091A	7/9/2007 6:33:06 nu	0.421	0.265 (55845)
15	015A	7/9/2007 6:33:06 nu	0.453	0.259 (55848)
50	050A	7/9/2007 6:33:06 nu	0.484	0.254 (55848)
20	020A	7/9/2007 6:33:06 nu	0.265	0.251 (55836)
70	070A	7/9/2007 6:33:06 nu	0.484	0.247 (55837)
19	019A	7/9/2007 6:33:06 nu	0.484	0.245 (55848)
40	040A	7/9/2007 6:33:06 nu	0.500	0.240 (55848)
38	038A	7/9/2007 6:33:06 nu	0.250	0.238 (55843)
73	073A	7/9/2007 6:33:06 nu	0.500	0.237 (55848)
49	049A	7/9/2007 6:33:07 nu	0.125	0.235 (55837)
42	042A	7/9/2007 6:33:06 nu	0.234	0.234 (55787)
1	001A	7/9/2007 6:33:06 nu	0.344	0.232 (55848)
91	091A	7/9/2007 6:33:06 nu	0.265	0.232 (55848)
89	089A	7/9/2007 6:33:06 nu	0.453	0.232 (55848)
95	095A	7/9/2007 6:33:06 nu	0.422	0.231 (55848)
44	044A	7/9/2007 6:33:06 nu	0.469	0.231 (55847)
17	017A	7/9/2007 6:33:07 nu	0.140	0.231 (55834)
36	036A	7/9/2007 6:33:06 nu	0.469	0.230 (55848)
55	055A	7/9/2007 6:33:06 nu	0.437	0.226 (55848)
88	088A	7/9/2007 6:33:07 nu	0.296	0.225 (55845)
2	002A	7/9/2007 6:33:07 nu	0.093	0.224 (55848)
46	046A	7/9/2007 6:33:06 nu	0.453	0.223 (55841)
32	032A	7/9/2007 6:33:06 nu	0.469	0.216 (55848)
92	092A	7/9/2007 6:33:06 nu	0.469	0.215 (55847)
14	014A	7/9/2007 6:33:06 nu	0.328	0.214 (55848)
33	033A	7/9/2007 6:33:06 nu	0.437	0.213 (55848)
60	060A	7/9/2007 6:33:06 nu	0.250	0.212 (55848)
58	058A	7/9/2007 6:33:07 nu	0.140	0.206 (55845)
93	093A	7/9/2007 6:33:06 nu	0.453	0.206 (55848)
77	077A	7/9/2007 6:33:06 nu	0.203	0.203 (55848)

Latency of incoming data:

Highest average values

Even the highest average values are satisfactory.

First Performance Tests



Synchronizer (all) : Status				
Synchronized output (Time/Stations): 7/9/2007 6:35:45 ru - 95				
ID	Station	Received	Delay [s]	Avg Delay [s] (E.p...)
82	082A	7/9/2007 6:35:45 ru	0.422	0.176 (66006)
12	012A	7/9/2007 6:35:45 ru	0.391	0.175 (66007)
63	063A	7/9/2007 6:35:45 ru	0.406	0.175 (66007)
37	037A	7/9/2007 6:35:45 ru	0.281	0.173 (65996)
67	067A	7/9/2007 6:35:45 ru	0.219	0.171 (66007)
75	075A	7/9/2007 6:35:45 ru	0.203	0.168 (66007)
11	011A	7/9/2007 6:35:45 ru	0.266	0.168 (66007)
10	010A	7/9/2007 6:35:45 ru	0.375	0.168 (66007)
90	090A	7/9/2007 6:35:45 ru	0.406	0.168 (66007)
77	077A	7/9/2007 6:35:45 ru	0.281	0.166 (66007)
29	029A	7/9/2007 6:35:45 ru	0.406	0.165 (66007)
61	061A	7/9/2007 6:35:45 ru	0.141	0.165 (66005)
53	053A	7/9/2007 6:35:45 ru	0.156	0.164 (66005)
84	084A	7/9/2007 6:35:45 ru	0.250	0.164 (65978)
97	097A	7/9/2007 6:35:45 ru	0.375	0.163 (66002)
79	079A	7/9/2007 6:35:45 ru	0.172	0.157 (66007)
26	026A	7/9/2007 6:35:45 ru	0.391	0.157 (66007)
23	023A	7/9/2007 6:35:45 ru	0.156	0.154 (66007)
34	034A	7/9/2007 6:35:45 ru	0.109	0.152 (66007)
28	028A	7/9/2007 6:35:45 ru	0.375	0.149 (66007)
4	004A	7/9/2007 6:35:45 ru	0.141	0.148 (66007)
71	071A	7/9/2007 6:35:45 ru	0.219	0.146 (66006)
39	039A	7/9/2007 6:35:45 ru	0.250	0.145 (66007)
64	064A	7/9/2007 6:35:45 ru	0.375	0.144 (66007)
25	025A	7/9/2007 6:35:45 ru	0.234	0.140 (66007)
6	006A	7/9/2007 6:35:45 ru	0.172	0.137 (66007)
48	048A	7/9/2007 6:35:45 ru	0.172	0.137 (66007)
54	054A	7/9/2007 6:35:45 ru	0.141	0.136 (66007)
3	003A	7/9/2007 6:35:45 ru	0.141	0.127 (66007)
8	008A	7/9/2007 6:35:45 ru	0.359	0.125 (66007)
7	007A	7/9/2007 6:35:45 ru	0.094	0.121 (66007)
98	098A	7/9/2007 6:35:45 ru	0.000	0.024 (66007)

Latency of incoming data:

Lowest average values

All current values fulfill the specified requirement, that delays must be less than 1 sec.

← RS at Control Center



Thank you for your attention



Dr. Michail Gianniu
 Head of Geodetic Department
 KTIMATOLOGIO S.A.
 339 Mesogion Ave.
 15562 Holargos
 Greece
 Tel. +30-210-6505832
 Email: mgianniu@ktimatologio.gr

